

## DESCRIPTION

Johnstone's Trade Acrylic Durable Matt is for use on interior walls and woodwork, including surfaces susceptible to condensation. Its Nonyellowing smooth appearance is harder, therefore easier to clean than conventional emulsions. A fast drying, low odour alternative to traditional eggshell; it is ideal for use where minimum disruption is important.

## RECOMMENDED USES

**INTERIOR** Suitable for interior use.



## TYPE OF SUBSTRATE

Interior walls and ceilings. Suitably primed woodwork and radiators.

## COLOUR RANGE

Over 16,000 colours are available via the Johnstone's Tinting System.

## FINISH

Matt.

## VOLUME SOLID

33.6%

## COVERAGE

**COVERAGE** Johnstone's Trade Acrylic Durable Matt will cover approximately 11-13 square metres per litre depending on the nature and porosity of the surface. If more than one can of a colour is to be used in the same area, intermix before use.



## FILM THICKNESS

Wet: 83µm, dry: 28µm.

## DRYING TIME

**RECOAT** Touch dry in 1-2 hours. Allow 4 hours before applying a second coat if required. Do not apply when air or surface temperature is below 10°C or in damp conditions.



## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST

## THINNER

Thinner: Clean Water

## VOC CONTENT

EU Limit Value for this product (Cat A/a): 30g/l (2010) This product contains max 10g/l VOC



## KEY PROPERTIES

- Tough, durable & washable.
- Ideal for high wear/traffic areas.
- Resists moisture & Non-yellowing.
- Class 1 Scrub Rating – ISO11998
- Mould resistant formulation\*

## PREPARATION

All surfaces should be sound, clean, dry and free from grease. Remove any crazed or flaking paint. Rub down sound glossy surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact PPG Extra. Seal absorbent surfaces with a solution of up to 1 part water to 4 parts Johnstone's Trade Acrylic Durable Matt. Prime bare timber and metal surfaces with an appropriate Johnstone's Trade primer. Allow radiators to cool before painting. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com).

## APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well before use and apply by brush, roller or paint pad. Also suitable for applying by spray. When using a roller, use a medium pile synthetic type. Do not overfill the tray. Ensure roller is loaded evenly. If using a brush, load generously. Apply liberally and evenly; avoid overspreading.

## CLEANING



Remove as much product as possible from equipment before cleaning. Clean immediately after use in warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty waste paint into drains or watercourses.

## PRECAUTIONS

- Keep out of reach of children
  - Avoid contact with skin and eyes
  - Do not ingest
  - Do not breathe spray. Wear respiratory protection
  - If medical advice is needed have container or label to hand
  - Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
  - SDS available : [www.johnstonestrade.com](http://www.johnstonestrade.com) or call 01924 354354
- \*Johnstone's Trade Acrylic Durable Matt contains a biocide to protect paint surface from mould degradation.

## SIZES

2.5 Litre, 5 Litre and 10 Litre\*

\* 10L available in BW and Magnolia only