

Flat Oil Paint

DESCRIPTION

Johnstone's Trade Flat Oil Paint is a solvent-borne traditional matt finish formulated for interior use on wood or metal surfaces. Based on an alkyd resin it provides excellent obliteration and flow characteristics and produces a durable, smooth even finish.

RECOMMENDED USES



Wood and metal surfaces.

SPECIAL PROPERTIES

Suitable on a wide range of suitably primed substrates.

COLOUR RANGE

Brilliant White.

FINISH

VOLUME SOLID

Matt.

49%.

COVERAGE



Johnstone's Trade Flat Oil Paint will cover approximately 16-18 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 80µm, dry: 40µm.

DRYING TIME



Recoatable after 16-24 hours under normal drying conditions.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position.. STORE AWAY FROM HEAT AND FLAME.

THINNER

Cleaner: White Spirit.

VOC CONTENT

EU limit value for this product (Cat A/d): 300g/l (2010) This product contains max 300g/l VOC



KEY PROPERTIES

- · Excellent obliteration and flow characteristics
- · Outstanding durability
- · Dries to an attractive matt finish

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare surfaces with the appropriate Johnstone's Trade Specialist Primer. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhaltion of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure maximum ventilation during application and drying. Not recommended for interior use on large surface areas, or in confined spaces. Stir well before use. Easy to apply by brush or roller.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- \bullet If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/ transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZE

2.5 Litre

