

## DESCRIPTION

Johnstone's Trade UltraFlat Matt is a broadwall emulsion, that leaves a uniform flat matt finish, irrespective of lighting conditions, making it ideal for walls and ceilings. The low reflectance technology and ultra fine texture eliminates flashing\* and also gives you the best opportunity of an invisible spot repair.

\*Application in accordance with BS 6150:2019 and manufacturer's instructions

## KEY PROPERTIES

- Eliminates Flashing \*
- Excellent Touch-up
- Flat Matt Finish – Ideal for critically lit areas and ceilings

## RECOMMENDED USES



Internal finish for all types of Interior walls and ceilings, both bare and previously painted, including plaster, plasterboard, concrete, dry lining, ceiling tiles and wallcoverings etc. Ideal, where the surface and site conditions are subject to critical lighting and potential touch-ups.

## COLOUR RANGE

Available in Brilliant White and L Base only

## FINISH

Flat Matt Finish  
(2% Sheen Level)

## VOLUME SOLID

26.51 %

## COVERAGE



Johnstone's Trade UltraFlat Matt will cover up to 13 square metres per litre depending on the nature and porosity of the surface being painted.

## FILM THICKNESS

WET: 105 um DRY: 27 um

## DRYING TIME



Touch Dry in 1-2 hours.  
Recoat after 2-4 hours, under normal conditions

## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Lift with care. PROTECT FROM FROST.

## THINNER

Thinner: Clean Water

## VOC CONTENT

EU limit value for this product (Cat A/a):  
30g/l (2010)  
This product contains max 10g/l VOC



## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down previously glossed painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation or pre-1960s paint surfaces over wood and metal as they may contain harmful lead. Seal absorbent surfaces with a coat of Johnstone's Trade UltraFlat Matt thinned up to 5-10% with clean water. For more information and free Johnstone's Trade Datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com).

## APPLICATION



Ensure good ventilation during application and drying. Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Do not breathe spray. Wear respiratory protection. If more than one of a colour is to be used in the same area, intermix before use. When attempting a wide colour change, additional coats may be required. Do not apply in temperatures below 8°C.

## SPRAY APPLICATION

Airless spray application: undiluted, spray @ 2000-2500 PSI with 0.013"-0.017" tip.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses. Do not use empty container for storing food (10L ONLY)

## PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : [www.johnstonestrade.com](http://www.johnstonestrade.com) or call 01924 354354

## SIZES

5 and 10 litre